

The VCA Vagabond Battery Charger Car Adaptor

The VCA is a **DC/AC adaptor** that plugs into your car's cigarette lighter outlet, allowing you to recharge your Vagabond II Battery (B20A) or your Vagabond I Battery (B15A) from your car's battery.

Note: The VCA is used solely to charge the Vagabond internal battery from your car's battery. The VCA may not be used to power your flash units or power packs directly.

Using the VCA with the Vagabond Battery Charger:

- 1. Turn your Vagabond system OFF.** With the Vagabond II, turn the system off by placing the SLOW / OFF / FAST switch in the center "OFF" position. With the Vagabond I, turn the ON / OFF switch on to the "OFF" position on your CU-150 unit(s).
- 2. Insert the VCA Vagabond Battery Charger Car Adaptor** into your car's cigarette lighter / auxiliary outlet. Ensure that the fit is tight and that the adaptor is pressed all the way inside the outlet. The **Green Power Indicator Light** on the top of the VCA will illuminate when the contact is secure and power is applied.
 - ** If the fit is too loose when you insert the VCA inside the outlet, remove the VCA and slide the adjuster to the "L" position. In the "L" position, the two side spring sheets will expand. Plug the adaptor back into the outlet and ensure that the fit is tight.
 - ** With some vehicles, it may be necessary to turn the **ignition switch** to the "accessory" position to apply power to the cigarette lighter / auxiliary outlet.
- 3. Connect the battery charging cord to the Vagabond system.** With the Vagabond II system, plug the battery charging cord into the battery charging outlet on the PSI900 control panel (the outlet is labeled "100-260 VAC CHARGER IN"). With the Vagabond I system, locate the VBC Vagabond Battery Charger and its AC power cord in the front flap pocket of your Vagabond Carrying Bag. Plug the VBC Charger's AC power cord into the two-pin appliance receptacle at the end of the VBC housing.
- 4. Connect the battery charging cord to the VCA.** Plug the battery charging cord (Vagabond II) or VBC AC power cord (Vagabond I) into the AC outlet on the VCA adaptor. This will begin charging your battery. Using the VCA will allow your battery to recharge normally.
 - ** Vagabond II users can turn the system on and **continue to use the Vagabond II while charging** the B20A battery from the car's battery. Please be aware that the VCA may get very hot to the touch if the system is in use while the battery is recharging.
 - ** Vagabond I users **must not attempt to use the Vagabond I system** while the battery is charging.

Paul C. Buff

Paul C. Buff, Inc. • 2725 Bransford Avenue Nashville, Tennessee 37204
Toll Free 1-800-443-5542 • Local (615) 383-3982 • Fax (615) 383-0676

